
LAKELAND® FIRE + SAFETY

BATTALION™ PROXIMITY TURNOUT GEAR





Battalion Proximity Gear Materials

- **Outer shell**
  05WKRS9-60-AL8: 7.8oz±0.5oz per square yard, aluminized PyroTex® / Kevlar® Ripstop knit Fabric.
- **Moisture Barrier**
  Stedair 3000: Nomex laminated to an ePTFE membrane. A combination of microporous and monolithic barriers.
- **Thermal Liner**
  Q-8®: Meta-Aramid / FR Rayon batt quilted to a Meta-Aramid / FR Modacrylic plain weave facecloths. (135S)

NFPA1970(1971)-2025

Thermal Protective Performance(TPP) ≥41.5 ,
Radiant Heat Reflectance >95%



135S

Coat（PBA3225/LOBC 97）

- 32" Length Coat.
- Plastic Delrin® YKK® Zipper/Velcro® Closure.
- Easy Grip™ DRD.
- Low Profile 3" Collar with Hanger Loop.
- Set-In Pleated Ergonomically Curved Sleeves.
- 7" Black Nomex® Thumbhole Wristers.
- 5" Deep Sleeve Wells.
- Coat Cuff Reinforcements.
- 2" x 8" x 8" Coat Expansion Pockets.
- Liner Inspection Velcro Opening.

Pants（PBA3325/LOBP97）

- Low-Rise Waist Design with small 3" Rear Bib for Overlap.
- Pant Closure: Hook & Dee, Snap with Velcro® Fly Closure.
- 2" x 10" x 10" Pant Expansion Pocket lined with Kevlar®
- Double Padded Knees with outer shell fabric.
- Pant Cuff Reinforcements.
- Reverse Boot Cut.
- 135S Black-Ops Multi Adjust Suspenders.

Coat

	SM		M		L		XL		2X		3X		4X	
CHEST	34	36	38	40	42	44	46	48	50	52	54	56	58	60
SLEEVE	32.5"	33.25"	33.75"	34.5"	35"	35.75"	36.5"	37.25"	38"	38.75"	39.5"	40.25"	41"	41.75"

Pants

	SM		M		L		XL		2X		3X		4X	
WAIST	30	32	34	36	38	40	42	44	46	48	50	52	54	56

Certificate Number:20260310-MH15305
Report Reference: MH15305-20260310

Lakeland Asia Pacific
Email: sales-ap@lakeland.com
Web: www.lakelandfire.com